

L-421-06

BLACK-TOPPER®

Shooter II Series™ Asphalt Distributor



Black-Topper® Shooter II™

Truck Mounted Distributor



1000, 1500, 1750 and
2000 gallon
capacities



Designed for dependability, economy and safe operation.



Mounted on single axle chassis or skid mounted for shipping. Includes a side mounted ladder to manhole and a tank contents gauge visible from both cab and rear loading area. Flanged aluminium fenders and FMVSS-108 lights and wiring insure safe, efficient travel.



Tank constructed of a 10 gauge steel shell with dished and flanged heads and full section surge plates. Spill collar with 20" manhole with strainer and rollover protection meet HM-198A/HM 183 DOT hot asphalt requirements. Fiberglass 2" insulation covered with aluminium jacketing.



Asphalt circulating system includes cab control automatic valves for circulation and spray. Pump inlet contains a removable strainer. System includes all valves for loading, circulating in tank, circulating in bar, spraying, hand spray, transfer and unloading.

Etnyre ShooterTM II features provide reliability and easy operation.



Solid pipe feed lines. Pump, valves, and circulating system are manufactured by Etnyre to minimize exposed lines, heat loss and sumps.



Heating system options provide a choice of either one or two flues and LPG or high pressure fuel oil burners. Portable burners and outfire protection for LPG burners are also available.



Full circulating 12' spray bar with 8' center section and folding wings is standard. Widths up to 16' are optional. All bars include individual one foot electric over air cab controls and break-away joints, electric/hydraulic lift and shift. Manual flip valves control nozzles on 4" centers.



Computer control of asphalt application is standard equipment. Includes full cab controls for all asphalt valve, and spray bar functions. Straight forward, one man operation.



Truck mounted hydrostatic pump and high torque motor drive the proven Etnyre 400 GPM asphalt pump. The system includes a 25 gallon flushing tank with line to asphalt pump.



Versatile handspray attachment is standard equipment, allows greater efficiency on all maintenance jobs. For finishing intersections, patching, and surfacing in limited areas. Includes hand spray gun with triple lap 3 nozzle spray and 25' of asphalt grade hose.



One man cab control with additional rear control panel for easy loading.



Easy operation and maximum efficiency.

Request the following items for more information about the Etnyre Shooter:

- SMU-421 Specifications for Black-Topper Shooter
- A-421 Features for Black-Topper Shooter
- V-421 Etnyre Black-Topper Shooter Video

Distributed By:

E. D. Etnyre & Co., whose policy is one of continuous improvement, reserves the right to change specifications without notice. Some items shown in photos and illustrations may be optional equipment.



E. D. ETNYRE & CO.,
1333 South Daysville Road, Oregon, Illinois 61061
Phone: 800-995-2116 or 815/732-2116 • Fax 815-732-7400
Web Site: www.etnyre.com • Email: sales@etnyre.com

Litho in U.S.A. **L-421-06**