

Platform Length:	22'-0" (Clear, unobstructed)
Platform Width:	8'-6" (102")
Deck Construction:	(4) 16" deep/full length one piece (no splices) I-Beams; 100,000 p.s.i. flange construction (fully cambered beams). Tapered top and bottom first 9'.
Crossmembers:	One (1) piece junior I-beams M8" x 6.5# pierced through mainbeams on 20" centers.
Outriggers:	12" Heavy duty cast steel, swinging and removable type, w/double hook-on removable in the first position.
Deck Height:	22" Loaded; adjustable 16", 18", 20", 22", 24"
Road Clearance:	6" Loaded; adjustable 0", 2", 4", 6", 8"
Lash Rings:	Eight (8) 1" forged rings (bent style), 4 each side of deck.
Lashing Slots:	Two (2) - One (1) on bottom side outside edge of bolsters.
Flagholder Slots:	Four (4) - One (1) on each end of bolsters and half bolsters.
Decking:	1-1/2" apitong, outside of mainbeams attached by self tapping screws.
Ramps:	31" Front folding ramps steel, double hinged, traction bars.
Rear Loading Features:	41° sloped ramp ahead of tires, wide center full load bearing drop bolsters between axles, rear load bearing bolster after 2nd axle.
Suspension:	Ridewell air ride w/+3"/-3" height adjustment in 1-1/2" increments and manual exhaust valve.
Axles:	Two (2) 22,500# capacity (full width) with 5/8" wall on 55" axle centers. Includes override chains on all axles.
Wheels:	Steel disc, hub piloted type, outboard mount with oil seals, white.
Tires:	8-255/70R 22.5 (H) 16 P.R. Radials.
Anti-Lock Brakes:	2S/2M (2-sensors and 2-modulators).
Brakes:	16-1/2" x 7" air with automatic slack adjusters w/spring brakes on rear axle. Brake rating at a minimum 20,000# per axle.
Boomwell:	Recessed boomwell (open) over axles #1 and #2 and rear half bolster.
Lights and Wiring:	Truck-Lite® L.E.D. sealed system.
Paint:	Shot blast, clean, prime, paint with (2-part urethane) black, red or yellow standard finish.
Mudflaps:	Rubber type rear of axle #2.